



Ground Support Equipment | **5ft. Dollies**

# CD-04

CONTAINER DOLLY

## Dimensions

<b>Maximum length</b>	3993 mm
<b>Maximum width</b>	1756 mm
<b>Tara Weight</b>	844 kg
<b>Max load</b>	2450 kg
<b>Suitable for</b>	LD1, LD2, LD3, LD4, LD8

## Specification

<b>Finish</b>	Hot dip galvanised
<b>Turntable deck</b>	Yes
<b>Type of rollers</b>	Cargo rollers Ø89 mm, spring loaded
<b>Tow-Bar</b>	1100 mm
<b>Tow-Eye diameter</b>	Ø40 mm
<b>Parking brake</b>	On front wheels, activated when in upwards position
<b>Type of steering</b>	Turntable steering, 2 wheel steering
<b>Tyres</b>	4
<b>Wheel type (dia)</b>	3.00 D / 4.00 x 8 or 15 x 4.5 - 8
<b>Maximum speed (unloaded)</b>	25 km/h
<b>Type of loading</b>	Narrow Edge Loading
<b>Coupling</b>	SPS E-Hitch

## Options

<b>Coupling</b>	Ringfeder, Rockinger
-----------------	----------------------

The specified dimensions and weight are indicative and no rights can be derived from this publication.

### Do you need a custom solution?

Our team of design experts and highly professional manufacturers will help by creating and planing the best solution for your need.

SPS BV Toekanweg 2, 1118 EB Schiphol, The Netherlands  
Phone: +31 20 354 00 63 | Mail: info@s-p-s.aero

SPS BV Toekanweg 2

