



Ground Support Equipment | **10ft. Dollies**

CT-11

CARGO DOLLY

Dimensions

| | |
|-----------------------|----------------------|
| Maximum length | 5157 mm |
| Maximum width | 2650 mm |
| Tara Weight | 1375 kg |
| Max load | 6800 kg |
| Suitable for | LD7, LD9, P1, P2, P6 |

Specification

| | |
|---------------------------------|--|
| Finish | Hot dip galvanised |
| Turntable deck | No |
| Type of rollers | Cargo rollers Ø89 mm, spring loaded |
| Tow-Bar | 1836 mm |
| Tow-Eye diameter | Ø40 mm |
| Parking brake | On rear wheels, activated when in upright position |
| Type of steering | Ackerman steering, 2 wheel steering |
| Tyres | 4 |
| Wheel type (dia) | 365 x 160 - 220 |
| Maximum speed (unloaded) | 25 km/h |
| Type of loading | Narrow Edge Loading |
| Coupling | SPS E-Hitch |

The specified dimensions and weight are indicative and no rights can be derived from this publication.

Do you need a custom solution?

Our team of design experts and highly professional manufacturers will help by creating and planing the best solution for your need.

SPS BV Toekanweg 2, 1118 EB Schiphol, The Netherlands
Phone: +31 20 354 00 63 | Mail: info@s-p-s.aero

SPS BV Toekanweg 2

