



Ground Support Equipment | 10ft. Dollies

# CT-20

CARGO DOLLY

## Dimensions

<b>Maximum length</b>	4620 mm
<b>Maximum width</b>	3460 mm
<b>Tara Weight</b>	1345 kg
<b>Max load</b>	6800 kg
<b>Suitable for</b>	LD4, LD8, MH1, FQA, PMC

## Specification

<b>Finish</b>	Hot dip galvanised
<b>Turntable deck</b>	Yes
<b>Type of rollers</b>	Cargo rollers Ø89 mm, bolted
<b>Tow-Bar</b>	1100 mm
<b>Tow-Eye diameter</b>	Ø50 mm
<b>Parking brake</b>	On front wheels, activated when in upright position
<b>Type of steering</b>	Turntable steering
<b>Tyres</b>	4
<b>Wheel type (dia)</b>	3.00 D / 15 x 4,5 - 8
<b>Maximum speed (unloaded)</b>	25 km/h
<b>Type of loading</b>	Narrow Edge Loading
<b>Coupling</b>	SPS E-Hitch

## Options

<b>Coupling</b>	Ringfeder, Rockinger
-----------------	----------------------

The specified dimensions and weight are indicative and no rights can be derived from this publication.

### Do you need a custom solution?

Our team of design experts and highly professional manufacturers will help by creating and planing the best solution for your need.

SPS BV Toekanweg 2, 1118 EB Schiphol, The Netherlands  
Phone: +31 20 354 00 63 | Mail: info@s-p-s.aero

SPS BV Toekanweg 2

